


SB Type



SB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AB 0090 E0

Type: SB, Shaft diameter: 7, Outside diameter: 20, Width: 7

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
7	20	7	AB 0090 E0	—	—	—
8	18	7	AB 0145 E0	—	—	—
8	18	9	AB 0147 F0	—	—	—
8	22	7	AB 0158 E0	—	—	AB 0158 A3
9	22	7	AB 0205 E0	—	—	—
10	20	7	AB 0260 E0	—	—	—
10	21	8	AB 0267 E0	—	—	—
10	22	8	AB 0271 F0	—	—	—
10	25	7	AB 0279 E0	—	—	AB 0279 A3
10	30	7	AB 0288 E0	—	—	—
11	22	7	AB 0308 E2	—	—	—
12	22	7	AB 0371 E0	—	—	—
12	25	7	AB 0382 E0	—	—	AB 0382 A5
12	28	7	AB 0387 E0	—	—	—
12	30	9	AB 0393 E0	—	—	—
12	32	6	AB 0398 E0	—	—	—
13	25	7	AB 0473 E1	—	—	—
13	28	7	AB 0478 E0	—	—	—
14	24	6	AB 0514 E0	—	—	—
14	28	7	AB 0526 E0	—	—	—
15	24	7	AB 0584 E0	—	—	—
15	25	7	AB 0588 F0	—	—	—
15	28	7	AB 0592 E0	—	—	—
15	30	7	AB 0598 E0	—	—	AB 0598 A4
15	32	7	AB 0603 E0	—	—	—
15	32	9	AB 0604 E0	—	—	—
15	35	7	AB 0610 E0	—	—	—
16	26	7	AB 0678 E0	—	—	—
16	28	7	AB 0685 E0	—	—	—
16	30	7	AB 0687 E0	—	—	AB 0687 A4
16	35	9	AB 0698 E0	—	—	—
17	28	7	AB 0736 F0	—	—	—
17	30	6	AB 0742 G0	—	—	—
17	30	8	AB 0745 G0	—	—	—
17	32	8	AB 0751 E0	—	—	—
17	35	7	AB 0759 E0	—	—	—
17	35	8	—	—	—	AB 0760 A3
17	38	7	AB 0768 E0	—	—	—
17	40	8	AB 0771 E1	—	—	—
18	30	7	AB 0816 E0	—	—	—
18	30	8	AB 0817 E0	—	—	—
18	35	8	AB 0829 E0	—	—	AB 0829 A3
18	35	9	AB 0831 E0	—	—	—
19	30	8	AB 0864 E0	—	—	—
19	38	7	AB 0880 E0	—	—	—

SB Type



SB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.

■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AB 0881 E0


Type: SB, Shaft diameter: 19, Outside diameter: 38, Width: 10

14

SB type

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
19	38	10	AB 0881 E0	—	—	—
19	40	10	AB 0883 E0	—	—	—
20	30	7	AB 0984 H0	—	—	—
20	30	9	AB 0987 E0	—	—	—
20	32	8	AB 0997 E0	—	—	—
20	35	7	AB 1012 E0	—	—	—
20	35	8	AB 1013 E0	—	—	AB 1013 A3
20	36	7	AB 1017 F0	—	—	—
20	36	10	AB 1019 E0	—	—	—
20	40	7	AB 1029 E0	—	—	—
20	40	8	AB 1030 E3	—	—	—
20	40	10	AB 1032 E0	—	—	—
20	40	11	AB 1033 F0	—	—	AB 1033 A3
20	42	10	AB 1038 E0	—	—	—
20	45	12	AB 1045 E0	—	—	—
21	35	7	AB 1084 E0	—	—	—
22	32	7	AB 1116 E0	—	—	—
22	35	7	AB 1126 E0	—	—	—
22	35	8	AB 1127 E0	—	—	—
22	36	10	AB 1130 E0	—	—	—
22	38	8	AB 1133 E0	—	AB 1133 F0	—
22	40	8	AB 1138 E1	—	—	—
22	40	10	AB 1140 E0	—	—	—
22	42	7	AB 1145 E0	—	—	—
22	42	11	AB 1148 E0	—	—	—
23	42	7	AB 1223 E0	—	—	—
23	42	11	AB 1224 E0	—	—	—
24	38	8	AB 1252 E0	—	—	—
24	38	10	AB 1255 E0	—	—	—
24	40	8	AB 1260 E0	—	—	AB 1260 A4
24	45	7	AB 1265 E0	—	—	—
25	37	8	AB 1302 F0	—	—	—
25	38	7	AB 1306 E0	—	—	—
25	38	8	AB 1307 E0	—	—	—
25	40	8	AB 1314 F0	—	AB 1314 H0	AB 1314 A3
25	40	10	AB 1315 E0	—	—	—
25	42	8	AB 1322 E0	—	—	—
25	45	8	AB 1335 F0	—	—	—
25	45	10	AB 1337 F0	AB 1337 G0	—	—
25	45	11	AB 1338 E0	—	AB 1338 G2	AB 1338 A3
25	47	6	AB 1348 E0	—	—	—
25	47	10	AB 1352 E0	—	—	—
25	50	9	AB 1361 E0	—	—	—
25	50	12	AB 1363 E0	—	—	—
25	52	10	AB 1377 E0	—	—	—

SB Type



SB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AB 1379 E0

Type: SB, Shaft diameter: 25, Outside diameter: 52, Width: 12

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
25	52	12	AB 1379 E0	—	—	—
26	36	8	AB 1459 E0	—	—	—
26	38	8	AB 1464 E0	—	—	—
26	40	8	AB 1468 E0	—	—	—
26	42	8	AB 1474 F0	—	—	—
27	40	8	AB 1508 E0	—	—	—
27	43	9	AB 1512 E0	—	—	—
27	47	11	AB 1518 E0	—	—	—
28	38	7	AB 1531 E0	—	—	—
28	38	8	AB 1532 E1	—	—	—
28	40	8	AB 1538 E0	—	—	—
28	42	8	AB 1544 E0	—	—	—
28	44	11	AB 1546 G1	—	—	—
28	45	8	AB 1550 E0	—	—	—
28	48	11	AB 1563 E0	—	—	AB 1563 A3
30	39	7	AB 1651 F0	—	—	—
30	40	7	AB 1656 E0	—	—	—
30	42	8	AB 1666 E0	—	—	—
30	44	9	AB 1673 E0	—	—	—
30	45	8	AB 1679 G0	AB 1679 F0	AB 1679 E1	AB 1679 A3
30	45	9	AB 1680 E0	—	—	—
30	45	12	AB 1682 E0	—	—	—
30	46	9	AB 1689 E0	—	—	—
30	47	8	AB 1692 F0	—	—	—
30	47	10	AB 1693 E0	—	—	—
30	47	12	AB 1695 E0	—	—	—
30	48	8	AB 1700 E0	—	—	—
30	48	11	AB 1702 E0	—	—	—
30	50	7	AB 1704 F0	—	—	—
30	50	8	AB 1705 F0	—	AB 1705 E0	—
30	50	9	AB 1706 E0	—	—	—
30	50	10	AB 1708 E0	—	—	—
30	50	11	AB 1709 G0	—	—	AB 1709 A3
30	52	10	AB 1721 E0	—	—	—
30	55	12	AB 1736 E0	—	—	—
32	43	10	AB 1869 E0	—	—	—
32	44	9	AB 1871 E0	—	—	—
32	45	8	AB 1880 E0	—	—	—
32	46	8	AB 1884 E0	—	—	—
32	47	8	AB 1888 F0	—	—	—
32	48	8	AB 1894 E0	—	—	—
32	52	8	AB 1902 E0	—	—	—
32	52	11	AB 1904 E0	—	—	AB 1904 G1
33	50	7	AB 1933 E0	—	—	—
33	52	7	AB 1937 E0	—	—	—

SB Type



SB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.

■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AB 1968 E0


Type: SB, Shaft diameter: 34, Outside diameter: 48, Width: 8

14

SB type

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
34	48	8	AB 1968 E0	—	—	—
34	54	11	AB 1978 E0	—	—	—
35	47	7	AB 2041 F0	—	—	—
35	48	8	AB 2048 E0	—	—	—
35	50	7	AB 2056 E0	—	AB 2056 I0	—
35	50	8	AB 2057 G0	—	—	AB 2057 A7
35	50	10	AB 2059 E0	—	—	—
35	52	7	AB 2066 E0	—	—	—
35	52	10	AB 2069 E0	—	—	—
35	52	12	AB 2072 F0	—	—	—
35	55	8	AB 2081 E0	—	—	—
35	55	9	AB 2083 F0	—	AB 2083 E0	—
35	55	11	AB 2085 F0	—	AB 2085 H0	AB 2085 A3
35	58	9	AB 2099 E1	—	—	—
35	60	12	AB 2107 F0	—	—	—
35	62	10	AB 2118 E0	—	—	—
36	50	7	AB 2162 E0	—	—	—
36	50	10	AB 2164 E0	—	—	—
38	47	10	AB 7101 E0	—	—	—
38	50	8	AB 2218 E1	—	—	—
38	55	8	AB 2230 E0	—	AB 2230 F0	—
38	55	9	AB 2231 E0	—	—	—
38	58	7	AB 2238 E0	—	—	—
38	58	8	AB 2239 E2	—	—	—
38	58	11	AB 2240 G0	AB 2240 F0	—	AB 2240 A3
38	62	11	AB 2250 E0	—	—	—
40	52	8	AB 2343 E3	—	—	—
40	55	9	AB 2361 G0	—	—	—
40	58	8	AB 2369 F0	AB 2369 G0	—	AB 2369 A3
40	60	8	AB 2375 E0	—	—	—
40	60	10	AB 2377 E0	—	—	—
40	60	12	AB 2379 F0	—	—	—
40	62	7	AB 2385 E0	—	—	—
40	62	8	AB 2386 E0	—	—	—
40	62	11	AB 2388 F0	—	—	AB 2388 A3
40	62	12	AB 2390 H0	—	AB 2390 G2	—
40	65	10	AB 2402 E0	—	—	—
40	65	12	AB 2403 E0	—	—	—
42	55	9	AB 2483 E0	—	—	—
42	60	9	AB 2493 F0	AB 2493 E0	—	—
42	60	12	AB 2495 E0	—	—	—
42	65	9	AB 2504 E0	—	—	—
42	65	12	AB 2507 E0	—	—	AB 2507 A6
43	52	10	BB 2041 E0	—	—	—
44	56	7	AB 2551 E0	—	—	—

SB Type



SB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AB 2641 E0

Type: SB, Shaft diameter: 45, Outside diameter: 60, Width: 7

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
45	60	7	AB 2641 E0	—	—	—
45	60	9	AB 2643 F0	—	—	—
45	61	9	AB 2647 G0	AB 2647 F0	AB 2647 E0	—
45	62	9	AB 2651 F0	—	AB 2651 H0	AB 2651 A3
45	62	10	AB 2652 E0	—	—	—
45	62	12	AB 2653 E0	—	—	—
45	65	10	AB 2658 E0	—	—	—
45	68	9	AB 2666 F0	—	—	—
45	68	12	AB 2668 F0	AB 2668 G0	AB 2668 K3	AB 2668 A5
45	70	14	AB 2677 E0	—	—	—
45	72	12	AB 2685 E0	—	—	—
47	70	12	AB 2735 E0	—	—	—
48	62	9	AB 2775 E0	—	—	—
48	65	9	AB 2780 G0	—	—	—
48	70	9	AB 2788 E0	—	—	—
48	70	12	AB 2791 E0	AB 2791 F0	AB 2791 F1	AB 2791 A3
50	64	10	AB 2834 E0	—	—	—
50	65	9	AB 2838 E0	—	—	—
50	68	9	AB 2847 G0	—	AB 2847 F2	AB 2847 A3
50	70	10	AB 2854 G0	—	AB 2854 E0	—
50	70	12	AB 2857 E0	—	—	—
50	72	9	AB 2861 E0	—	—	—
50	72	10	AB 2862 E0	—	—	—
50	72	12	AB 2864 G0	AB 2864 H0	—	AB 2864 A3
50	74	12	AB 2872 E0	—	—	—
50	80	10	AB 2886 E0	—	—	—
50	80	12	AB 2887 F0	—	—	—
50	80	14	AB 2888 E0	—	—	—
51	62	7	AB 8924 E1	—	—	—
52	70	9	AB 2959 F0	—	—	—
52	75	9	AB 2965 E0	—	—	—
52	75	12	AB 2967 E0	—	—	AB 2967 A3
54	72	12	AB 3014 E1	—	—	—
55	70	9	AB 3036 F0	—	—	—
55	72	9	AB 3040 G0	—	AB 3040 F0	AB 3040 A3
55	78	9	AB 3053 E0	—	—	—
55	78	12	AB 3055 J0	AB 3055 G0	—	AB 3055 A6
55	80	12	AB 3062 E0	—	—	—
55	85	14	AB 3072 F0	—	—	—
56	78	12	AB 3094 E0	—	—	—
58	75	9	AB 3148 E0	—	—	—
58	80	9	AB 3152 G0	—	AB 3152 E0	AB 3152 F0
58	80	12	AB 3154 E0	AB 3154 F0	—	AB 3154 A5
60	75	9	AB 3193 F0	—	—	—
60	75	10	AB 3195 F0	—	—	—

SB Type



SB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AB 3204 F0

Type: SB, Shaft diameter: 60, Outside diameter: 78, Width: 9

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
60	78	9	AB 3204 F0	AB 3204 G0	AB 3204 E3	—
60	80	10	AB 3211 E0 ※	—	—	—
60	80	12	AB 3213 E0	—	—	—
60	82	9	AB 3220 E0	—	—	—
60	82	12	AB 3222 G0	AB 3222 H0	AB 3222 I3	AB 3222 A3
60	85	12	AB 3234 E0	—	—	—
60	90	14	AB 3244 E0	—	AB 3244 F1	—
62	80	9	AB 3290 F0	—	—	—
62	85	12	AB 3297 E0	—	—	AB 3297 A3
63	80	9	AB 3316 E0	—	—	—
63	85	9	AB 3320 E0	—	—	—
63	85	12	AB 3321 E1	—	—	—
65	82	10	AB 3389 E0	—	—	—
65	85	12	AB 3395 E0	—	—	—
65	88	12	AB 3400 F0	AB 3400 E1	AB 3400 E0	AB 3400 A3
65	90	10	AB 3406 E0	—	—	—
65	90	13	AB 3409 F0	AB 3409 H0	AB 3409 E0	AB 3409 G1
65	95	14	AB 3414 E0	—	—	—
68	90	12	AB 3459 F0	AB 3459 G0	—	AB 3459 A3
68	95	13	AB 3463 E0	—	AB 3463 F1	—
70	88	12	AB 3505 E0	—	—	—
70	90	10	AB 3512 E0	—	—	—
70	90	12	AB 3513 E0	—	—	—
70	92	12	AB 3519 G0	AB 3519 F1	AB 3519 F2	AB 3519 A3
70	95	13	AB 3527 G0	—	AB 3527 F2	AB 3527 A3
70	100	10	AB 3530 E0	—	—	—
70	100	14	AB 3532 G0	—	AB 3532 E0	—
71	95	13	AB 3549 E0	—	—	—
72	100	12	AB 3562 G0	—	—	AB 3562 F0
75	100	13	AB 3618 H0	AB 3618 A4	AB 3618 A7	AB 3618 A3
75	105	12	AB 3628 E0	—	—	—
75	105	15	AB 3631 E0	—	—	—
80	100	10	AB 3732 E0	—	—	—
80	100	13	AB 3734 E0	—	—	—
80	105	13	AB 3744 H0	AB 3744 A4	AB 3744 F2	AB 3744 A3
80	115	15	AB 3761 F0	AB 3761 E0	—	—
82	105	13	AB 3786 E0	—	—	—
85	105	15	AB 3837 E0	—	—	—
85	110	13	AB 3842 H0	—	—	AB 3842 A3
85	120	15	AB 3855 E0	—	—	—
88	115	13	AB 3879 E0	—	—	—
90	110	13	AB 3921 E0	—	—	—
90	115	13	AB 3932 H0	AB 3932 I0	AB 3932 G8	AB 3932 A5
90	115	15	AB 3934 E0	—	—	—
90	120	13	AB 3938 E0	—	—	—

SB Type



SB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AB 3944 E0

Type: SB, Shaft diameter: 90, Outside diameter: 125, Width: 15

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
90	125	15	AB 3944 E0	—	AB 3944 F0	—
90	130	13	AB 3948 E0	—	—	—
95	115	13	AB 3984 E0	—	—	—
95	120	13	AB 3994 F0	AB 3994 J0	AB 3994 G2	AB 3994 A3
95	125	14	AB 4000 E0	—	—	—
95	130	15	AB 4007 E0	AB 4007 F0	—	—
98	120	15	AB 4033 E0	—	—	—
100	120	12	AB 4055 E0	—	—	—
100	120	13	AB 4056 E0	—	—	—
100	125	13	AB 4063 A0	AB 4063 F0	AB 4063 E0	AB 4063 E1
100	125	15	AB 4065 E0	—	—	—
100	130	13	AB 4073 E1	—	—	—
100	130	15	AB 4074 E0	—	—	—
105	125	15	AB 4146 E0	—	—	—
105	130	13	AB 4150 E0	—	—	—
105	135	14	AB 4153 E0	AB 4153 G0	AB 4153 F3	AB 4153 A3 ※
105	140	15	AB 4161 E0	—	—	—
110	140	14	AB 4212 E0	AB 4212 F0	AB 4212 G0	AB 4212 A3 ※
110	140	15	AB 4213 E0	—	—	—
110	145	14	AB 4220 E0	—	—	—
110	145	15	AB 4221 E0	AB 4221 G0	AB 4221 F0	—
112	145	14	AB 4237 F0	—	—	—
115	145	14	AB 4282 A0	AB 4282 A1	AB 4282 E1	AB 4282 A3
115	150	16	AB 4292 E0	—	—	—
120	140	13	AB 4330 E1	—	—	—
120	150	14	AB 4346 A0	AB 4346 A5	AB 4346 A2	AB 4346 A3
120	155	16	AB 4355 E0	—	—	—
125	155	14	AB 4399 A0	—	AB 4399 E0	AB 4399 A3
125	160	16	AB 4404 E0	—	—	—
128	153	18	AB 4433 E0	—	—	—
130	160	14	AB 4451 A0	AB 4451 F0	AB 4451 E0	AB 4451 A3
130	160	15	AB 4452 E0	—	—	—
130	160	16	AB 4453 E0	—	—	—
130	170	15	AB 4464 E0	—	—	—
130	170	16	AB 4465 E0	—	—	—
135	165	14	AB 4498 E0	—	AB 4498 F1	AB 4498 A3
135	170	15	AB 4503 E0	—	—	—
140	170	14	AB 4542 A0	AB 4542 E3	AB 4542 E1	AB 4542 A3
140	185	16	AB 4558 E0	—	—	—
145	175	14	AB 4581 A0	AB 4581 A5	AB 4581 A2	AB 4581 A3
145	190	16	AB 4588 E0	—	—	—
150	180	14	AB 4624 A0	AB 4624 F0	AB 4624 E0	AB 4624 A3
150	195	20	AB 4635 E0	—	—	—
155	180	15	AB 4666 E0	—	—	—
155	185	15	AB 4669 E0	—	—	—

SB Type



SB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AB 4678 E1

Type: SB, Shaft diameter: 155, Outside diameter: 200, Width: 20

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
155	200	20	AB 4678 E1	—	—	—
160	190	14	AB 4711 E0	—	—	—
160	190	15	AB 4712 E0	—	—	—
160	190	16	AB 4713 A0	AB 4713 E0	AB 4713 H2	AB 4713 F0
160	200	14	AB 4719 E0	—	—	—
160	200	20	AB 4721 E0	—	—	—
160	210	20	AB 4724 E0	—	—	AB 4724 E1
165	220	20	AB 4753 E0	—	—	—
170	200	16	AB 4795 A0	—	—	AB 4795 A3
170	225	20	AB 4815 E0	—	—	—
175	230	20	AB 4855 E0	—	—	—
180	210	16	AB 4898 A0	—	AB 4898 E2	AB 4898 A6
180	215	16	AB 4904 E0	—	—	—
180	220	15	AB 4908 E1	—	—	—
180	225	20	AB 4913 E0	—	—	—
180	235	20	AB 4915 E2	—	—	—
190	220	14	AB 4974 F0	—	—	—
190	220	15	AB 4975 E0 ※	—	—	—
190	225	16	AB 4983 E0	—	—	AB 4983 A3
190	245	22	AB 4993 E0	—	—	—
200	230	15	AB 5053 P2	—	—	—
200	230	16	AB 5054 G0	—	—	—
200	230	18	AB 5056 E0	—	—	—
200	235	16	AB 5060 E6	—	—	—
200	240	16	AB 5065 E0	—	—	—
200	240	20	AB 5068 A0	—	—	AB 5068 A3
200	255	22	AB 5079 E0	—	—	—
205	260	23	AB 5113 E0	—	—	—
210	240	15	AB 5133 E0	—	—	—
210	250	16	AB 5138 E0	—	—	—
210	250	18	AB 5139 E0	—	—	—
210	250	20	AB 5140 A0	—	—	AB 5140 A3
210	265	23	AB 5146 E0	—	—	—
220	250	15	AB 5204 E0	—	—	—
220	255	16	AB 5207 E0	—	—	—
220	260	22	AB 5216 A0	—	—	AB 5216 A3 ※
220	275	23	AB 5224 E0	—	—	—
230	260	20	AB 5283 A0	—	—	AB 5283 A3 ※
230	285	23	AB 5296 E0	—	—	—
240	280	19	AB 5351 A0	—	—	AB 5351 A3 ※
250	280	15	AB 5398 E7 ※	—	—	—
250	310	25	AB 5412 A0	—	—	AB 5412 A3
260	320	25	AB 5471 A0	—	—	AB 5471 A3
270	330	25	AB 5523 A0	—	—	AB 5523 A3
280	320	18	AB 5560 E0	—	—	—

SB Type



Type: SB, Shaft diametaer: 280, Outside diameter: 340, Width: 28

[illegible]