


TB Type



TB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.

■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AD 0158 E0


Type: TB, Shaft diameter: 8, Outside diameter: 22, Width: 7

14

TB type

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
8	22	7	AD 0158 E0	—	—	AD 0158 A3
10	20	7	AD 0260 E1	—	—	—
10	25	7	AD 0279 E0	—	—	AD 0279 A3
12	22	7	AD 0371 E0	—	—	—
12	25	7	AD 0382 E0	—	—	AD 0382 A3
13	25	7	AD 0473 E0	—	—	—
14	28	7	AD 0526 E0	—	—	AD 0526 A4
15	25	7	AD 0588 G0	—	—	—
15	30	7	AD 0598 G0	—	—	AD 0598 A3
15	32	9	AD 0604 E0	—	—	—
16	26	7	AD 0678 F0	—	—	—
16	28	7	AD 0685 F0	—	—	—
16	30	7	AD 0687 H0	—	AD 0687 F1	AD 0687 A3
17	28	6	AD 0735 P0	—	—	—
17	30	8	AD 0745 E1	—	—	—
17	32	8	AD 0751 F0	—	AD 0751 E0	—
17	35	7	AD 0759 E0	—	—	—
17	35	8	AD 0760 E1	—	—	AD 0760 A3
17	38	7	AD 0768 E0	—	—	—
18	32	7	AD 0823 E0	—	—	—
18	35	8	AD 0829 F0	—	—	—
19	35	8	AD 0875 E0	—	—	AD 0875 A3
19	38	7	AD 0880 E0	—	—	—
19	38	10	AD 0881 E0	—	—	—
20	32	8	AD 0997 I1	—	—	—
20	35	7	AD 1012 F2	AD 1012 G0	—	—
20	35	8	AD 1013 E0	—	—	AD 1013 A3
20	35	10	AD 1015 F0	—	—	—
20	36	7	AD 1017 E0	—	—	—
20	40	7	AD 1029 F0	—	—	—
20	40	10	AD 1032 F0	—	—	—
20	40	11	AD 1033 F0	—	—	AD 1033 A3
20	45	12	AD 1045 E0	—	—	—
22	35	8	AD 1127 E0	—	—	—
22	38	8	AD 1133 F1	—	—	—
22	42	7	AD 1145 E0	—	—	—
22	42	10	AD 1147 F0	AD 1147 G0	—	—
22	42	11	AD 1148 F0	—	—	AD 1148 A4
23	42	11	AD 1224 E4	—	—	—
24	38	8	AD 1252 E0	—	—	—
24	40	8	AD 1260 E0	—	—	AD 1260 A3
24	45	10	AD 1266 F0	—	—	—
25	38	7	AD 1306 H1	—	—	—
25	38	8	AD 1307 E0	—	—	—
25	40	7	AD 1313 E3	—	—	—

TB Type



TB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AD 1314 F0

Type: TB, Shaft diameter: 25, Outside diameter: 40, Width: 8

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
25	40	8	AD 1314 F0	AD 1314 E0	—	AD 1314 A3
25	45	8	AD 1335 E0	—	—	—
25	45	10	AD 1337 G0	AD 1337 H0	—	—
25	45	11	AD 1338 E2	—	—	AD 1338 A3
25	47	8	AD 1351 E1	—	—	—
25	48	7	AD 1356 E0	—	—	—
25	50	14	AD 1364 E0	—	—	—
26	40	7	AD 1467 E0	—	—	—
26	40	8	AD 1468 E0	—	—	—
26	40	9	AD 1469 E0	—	—	—
26	42	8	AD 1474 E0	—	—	—
26	48	11	AD 1481 E0	—	—	—
27	47	11	AD 1518 H0	—	—	—
28	40	8	AD 1538 E0	—	—	—
28	44	8	AD 1545 E0	—	—	—
28	44	11	AD 1546 E0	—	—	—
28	45	8	AD 1550 F0	—	—	—
28	48	8	AD 1562 E0	—	—	—
28	48	11	AD 1563 E0	AD 1563 F0	—	AD 1563 A6
30	42	8	AD 1666 E0	—	—	—
30	44	7	AD 1671 G0	—	—	—
30	45	8	AD 1679 G0	AD 1679 F0	—	AD 1679 A3
30	45	11	AD 1681 E0	—	—	—
30	48	7	AD 1699 E0	—	—	—
30	50	8	AD 1705 E0	—	—	—
30	50	11	AD 1709 E0	AD 1709 F0	—	AD 1709 A3
30	52	8	AD 1720 E0	—	—	—
30	52	11	AD 1723 E0	—	—	—
32	45	8	AD 1880 E0	—	—	—
32	48	8	AD 1894 E0	—	—	—
32	52	8	AD 1902 E1	—	—	—
32	52	11	AD 1904 F0	—	—	AD 1904 A3
33	44	8	AD 1929 F1	—	—	—
34	54	11	AD 1978 E0	—	—	—
35	48	8	AD 2048 F0	—	—	—
35	50	8	AD 2057 G2	AD 2057 F0	—	AD 2057 A5
35	52	7	AD 2066 E0	—	—	—
35	52	11	AD 2071 E1	—	—	—
35	52	12	AD 2072 E0	—	—	—
35	55	8	AD 2081 F0	—	—	—
35	55	9	AD 2083 E0	—	—	—
35	55	11	AD 2085 G0	AD 2085 F0	AD 2085 N1	AD 2085 A3
35	60	12	AD 2107 E0	—	—	—
38	55	8	AD 2230 I0	—	—	—
38	55	9	AD 2231 E0	—	—	—

TB Type



TB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.

■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AD 2239 E0


Type: TB, Shaft diameter: 38, Outside diameter: 58, Width: 8

14

TB type

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
38	58	8	AD 2239 E0	—	—	—
38	58	11	AD 2240 I0	—	—	AD 2240 A3
40	52	8	AD 2343 E0	—	—	—
40	55	8	AD 2359 G0	—	—	AD 2359 H1
40	58	8	AD 2369 F0	—	—	AD 2369 A5
40	60	12	AD 2379 E0	—	—	—
40	62	8	AD 2386 E0	—	—	—
40	62	11	AD 2388 E0	AD 2388 P0	AD 2388 J1	AD 2388 F3
40	62	12	AD 2390 I0	—	—	—
40	65	12	AD 2403 E0	—	—	—
40	65	14	AD 2405 E0	—	—	—
40	68	11	AD 7424 E0	—	—	—
42	60	9	AD 2493 E0	—	—	—
42	65	9	AD 2504 E0	—	—	—
42	65	12	AD 2507 I0	—	AD 2507 K1	AD 2507 A3
45	60	9	AD 2643 G0	—	—	—
45	62	9	AD 2651 G0	AD 2651 F0	—	AD 2651 A3
45	62	12	AD 2653 E0	—	—	—
45	68	9	AD 2666 G1	—	—	—
45	68	12	AD 2668 G0	AD 2668 I0	—	AD 2668 A4
45	70	12	AD 2676 E0	—	—	—
45	70	14	AD 2677 E0	—	—	—
45	72	12	AD 2685 E0	—	—	—
48	65	9	AD 2780 G0	—	—	—
48	70	9	AD 2788 E0	—	—	—
48	70	12	AD 2791 E0	—	—	AD 2791 A3
50	65	9	AD 2838 F0	—	—	—
50	68	9	AD 2847 F0	—	—	AD 2847 A6
50	70	10	AD 2854 F0	—	—	—
50	72	9	AD 2861 E2	—	—	—
50	72	10	AD 2862 E0	—	—	—
50	72	12	AD 2864 G0	AD 2864 H0	—	AD 2864 A3
50	72	14	AD 2867 F0	—	—	—
50	80	14	AD 2888 F0	—	—	—
52	70	9	AD 2959 F0	—	—	—
52	75	12	AD 2967 E0	—	—	AD 2967 A3
55	72	9	AD 3040 F0	—	—	AD 3040 A6
55	72	12	AD 3042 E0	—	—	—
55	78	9	AD 3053 E0	—	—	—
55	78	12	AD 3055 H0	AD 3055 I0	AD 3055 J2	AD 3055 A3
55	80	12	AD 3062 E0	AD 3062 F0	—	—
55	85	14	AD 3072 E0	—	—	—
56	72	9	AD 3092 E0	—	—	—
56	78	12	AD 3094 E0	—	—	—
58	80	9	AD 3152 E0	—	—	—

TB Type



TB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AD 3154 F0

Type: TB, Shaft diameter: 58, Outside diameter: 80, Width: 12

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
58	80	12	AD 3154 F0	—	—	AD 3154 A3
60	75	9	AD 3193 F0	—	—	—
60	78	9	AD 3204 F0	—	—	—
60	80	12	AD 3213 F0	—	—	—
60	82	9	AD 3220 E0	—	—	—
60	82	12	AD 3222 I0	AD 3222 S0	—	AD 3222 A3
60	82	14	AD 3224 E0	—	—	—
60	90	14	AD 3244 E0	—	—	—
62	80	9	AD 3290 E0	—	—	—
62	85	9	AD 3295 E0	—	—	—
62	85	12	AD 3297 F4	AD 3297 E0	—	—
63	80	9	AD 3316 E0	—	—	—
63	85	12	AD 3321 E2	—	—	—
65	88	12	AD 3400 I0	AD 3400 K0	AD 3400 J2	AD 3400 A3
65	88	14	AD 3402 E0	—	—	—
65	90	13	AD 3409 J0	AD 3409 H0	AD 3409 G1	AD 3409 A5
65	95	16	AD 3415 E0	—	—	—
68	90	12	AD 3459 H0	AD 3459 E0	—	—
68	95	13	AD 3463 E9	—	—	—
70	88	12	AD 3505 H0	—	AD 3505 J1	—
70	92	12	AD 3519 K0	AD 3519 G0	—	AD 3519 A3
70	92	14	AD 3521 G0	—	—	—
70	95	13	AD 3527 H0	AD 3527 G1	AD 3527 G4	AD 3527 A3
70	100	14	AD 3532 E0	—	—	—
71	95	13	AD 3549 E0	—	—	—
72	94	10	BD 1423 E1	—	—	—
75	100	13	AD 3618 I0	AD 3618 J0	AD 3618 G2	AD 3618 A5
75	105	15	AD 3631 F0	—	—	—
75	110	13	AD 3636 E0	—	—	—
78	100	13	AD 3694 E0	—	—	—
80	105	13	AD 3744 J0	AD 3744 H0	AD 3744 F3	AD 3744 A3
80	105	15	AD 3746 E0	—	—	—
80	115	15	AD 3761 E1	—	—	—
85	110	13	AD 3842 I0	AD 3842 H1	AD 3842 G2	AD 3842 A3
85	110	15	AD 3844 F0	—	—	—
85	115	15	AD 3852 E0	—	—	—
85	120	15	AD 3855 E0	—	—	—
90	110	13	AD 3921 E0	—	—	—
90	115	13	AD 3932 J0	AD 3932 I1	AD 3932 G2	AD 3932 H0
90	125	15	AD 3944 E0	—	—	—
90	125	17	AD 3945 E0	AD 3945 F0	—	—
95	120	13	AD 3994 G0 ※	AD 3994 J0	—	AD 3994 A3
95	130	15	AD 4007 E3	—	—	—
95	130	17	AD 4008 E0	—	—	—
100	114	12	AD 7700 E0	—	—	—

TB Type



TB type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.

■When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AD 4063 A0


Type: TB, Shaft diameter: 100, Outside diameter: 125, Width: 13

14

TB type

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
100	125	13	AD 4063 A0	AD 4063 A1	AD 4063 A9	AD 4063 A4
100	125	15	AD 4065 F0	—	—	—
100	130	13	AD 4073 E1	—	—	—
100	135	15	AD 4079 E0	—	—	—
100	135	17	AD 4081 E0	—	—	—
105	135	14	AD 4153 A0 ※	AD 4153 A1	AD 4153 A4	AD 4153 A5
105	135	16	AD 4154 E0	—	—	—
110	140	14	AD 4212 A0 ※	AD 4212 A1	AD 4212 L0	AD 4212 A3
110	140	16	AD 4214 E0	—	—	—
110	145	15	AD 4221 E0	—	—	—
110	145	17	AD 4222 E0	—	—	—
112	145	14	AD 4237 E0	—	—	—
115	145	14	AD 4282 A0	AD 4282 G0	AD 4282 G2	AD 4282 A3
115	145	16	AD 4284 E0	—	—	—
115	150	16	AD 4292 E0	—	—	—
120	150	14	AD 4346 A0	AD 4346 A1	AD 4346 A2 ※	AD 4346 A9 ※
120	150	16	AD 4349 F0	—	—	—
120	155	16	AD 4355 E0	—	—	—
120	155	18	AD 4356 E0	—	—	—
125	155	14	AD 4399 A0	AD 4399 A1	AD 4399 A2	AD 4399 E1
125	155	16	AD 4400 F0	—	—	—
125	160	16	AD 4404 E0	—	—	—
125	160	18	AD 4405 E0	—	—	—
130	160	14	AD 4451 A0 ※	AD 4451 A1	AD 4451 A4	AD 4451 A3
130	160	16	AD 4453 E0	—	—	—
135	160	14	AD 4494 E0	—	—	—
135	165	14	AD 4498 A0	AD 4498 A1	AD 4498 G5	AD 4498 A6
135	175	16	AD 4506 E0 ※	—	—	—
140	170	14	AD 4542 A0	AD 4542 A1	AD 4542 A2	AD 4542 A3
140	180	16	AD 4555 E0	—	—	—
145	175	14	AD 4581 A0	AD 4581 A1	AD 4581 A2	AD 4581 F0
145	175	16	AD 4582 E0	—	—	—
145	176	14	AD 4584 E0	—	—	—
150	180	14	AD 4624 A0	AD 4624 A1	AD 4624 A8	AD 4624 A3
150	180	16	AD 4626 E0	—	—	—
155	200	20	AD 4678 F0	—	—	—
160	190	16	AD 4713 A4	—	—	AD 4713 A9
160	196	20	AD 4718 E0	—	—	—
170	200	16	AD 4795 A0	AD 4795 E0	—	AD 4795 A3
170	225	16	—	AD 4814 X0	—	—
170	225	20	AD 4815 F1	—	—	—
180	210	16	AD 4898 A9	AD 4898 E1	—	AD 4898 A3
180	215	18	AD 4905 E0	—	—	—
190	225	16	AD 4983 A9	—	—	AD 4983 A4
200	235	18	AD 5061 X4	AD 5061 X0	—	—

TB Type



- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an “*” at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.

Type: TB, Shaft diameter: 200, Outside diameter: 240, Width: 17

[illegible]