


TC_{Type}



TC type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AE 0090 A0

Type: TC, Shaft diameter: 7, Outside diameter: 20, Width: 7

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
7	20	7	AE 0090 A0	—	—	—
8	22	7	AE 0158 A4	—	AE 0158 A2	AE 0158 F2
8	25	8	AE 0164 E0	—	—	—
8	34	8	AE 0169 E0	—	—	—
9	22	7	AE 0205 A0	AE 0205 E0	—	—
9	28	8	AE 0210 E0	—	—	—
10	20	7	AE 0260 J0 ※	—	—	—
10	25	7	AE 0279 A6 ※	—	AE 0279 A2	—
10	28	8	AE 0285 E0	—	—	—
11	25	7	AE 0311 E0	—	—	—
11	30	10	AE 0315 E0	—	—	—
12	22	7	AE 0371 E0	AE 0371 L0	—	—
12	23	8	AE 0375 E0	—	—	—
12	25	7	AE 0382 A0 ※	—	AE 0382 A2	AE 0382 K1
12	28	7	AE 0387 E0 ※	—	—	—
12	30	9	AE 0393 E0	—	—	—
12	32	7	AE 0399 E1 ※	—	—	—
13	25	7	AE 0473 F0	—	—	—
13	28	7	AE 0478 A0	—	—	—
13	30	8	AE 0483 G0	—	—	—
14	25	7	AE 0519 E0 ※	—	—	—
14	28	7	AE 0526 A0 ※	—	—	AE 0526 F0
14	28	11	AE 0529 E0	—	—	—
14	32	9	AE 0536 E0	—	—	—
15	25	7	AE 0588 K1	—	—	—
15	30	7	AE 0598 A0	AE 0598 A1	—	—
15	30	10	AE 0600 E0	—	—	—
15	32	9	AE 0604 E0	—	—	—
15	35	7	AE 0610 F0	—	—	—
15	35	8	AE 0611 E1 ※	—	—	—
16	26	7	AE 0678 F1	—	—	—
16	28	7	AE 0685 G0	—	—	—
16	30	7	AE 0687 A0 ※	AE 0687 A1	AE 0687 A7	—
16	35	9	AE 0698 E0	—	—	—
17	30	7	AE 0743 E0	—	—	—
17	30	8	AE 0745 E8	—	—	—
17	32	7	AE 0750 E0	—	—	—
17	32	8	AE 0751 H6	—	—	—
17	35	7	AE 0759 E0	—	—	—
17	35	8	AE 0760 H5	—	AE 0760 A2	AE 0760 F0
17	35	10	AE 0761 F0	—	—	—
17	38	7	AE 0768 E0	—	—	—
17	40	9	AE 0772 E1	—	—	—
18	30	8	AE 0817 E0	—	—	—
18	32	7	AE 0823 E0 ※	—	—	—

TC Type



TC type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AE 0829 A0

Type: TC, Shaft diameter: 18, Outside diameter: 35, Width: 8

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
18	35	8	AE 0829 A0	—	AE 0829 A2	—
18	35	9	AE 0831 E0	—	—	—
18	38	7	AE 0838 E0	—	—	—
19	32	8	AE 0870 E0 ※	—	—	—
19	35	7	AE 0874 E1	—	—	—
19	35	8	AE 0875 A0	—	—	—
19	36	7	AE 0879 E0	—	—	—
19	38	7	AE 0880 E0	—	—	—
19	38	10	AE 0881 E0	—	—	—
20	30	7	AE 0984 H0	—	—	—
20	32	6	AE 0995 E0	—	—	—
20	32	8	AE 0997 E0 ※	—	—	—
20	34	7	AE 1003 E2	—	—	—
20	35	7	AE 1012 G0	AE 1012 J0	—	—
20	35	8	AE 1013 A4	AE 1013 E0	AE 1013 A2	AE 1013 F2
20	35	10	AE 1015 F0	—	—	—
20	36	7	AE 1017 F0	—	AE 1017 G1	—
20	37	7	AE 1020 E1	—	—	—
20	37	9	AE 1022 E1	—	—	—
20	37	10	AE 6758 E0	—	—	—
20	38	7	AE 1024 F0	—	—	—
20	40	7	AE 1029 E0	—	—	—
20	40	8	AE 1030 E1 ※	—	—	—
20	40	9	AE 1031 E0	—	—	—
20	40	10	AE 1032 G0	—	—	—
20	40	11	AE 1033 A0	—	—	—
20	42	8	AE 1037 E0	—	—	—
20	44	12	AE 1042 E0	—	—	—
20	45	8	AE 1043 E1	—	—	—
20	45	12	AE 1045 E0	—	—	—
21	38	8	AE 1089 E0	—	—	—
21	40	7	AE 1092 E2	—	—	—
22	35	8	AE 1127 E0	—	—	—
22	38	8	AE 1133 E0	AE 1133 F0	—	—
22	40	9	—	AE 1139 E0	—	—
22	40	11	AE 1141 E0	—	—	—
22	42	7	AE 1145 E0	—	—	—
22	42	10	AE 1147 E0 ※	—	—	—
22	42	11	AE 1148 A5	—	AE 1148 A2	—
23	42	11	AE 1224 A0	—	—	—
24	38	8	AE 1252 E0	—	—	—
24	38	10	AE 1255 E1	—	—	—
24	40	8	AE 1260 A0	AE 1260 A1	—	—
24	45	7	AE 1265 E3	—	—	—
24	45	10	AE 1266 E0	—	—	—

TC Type



TC type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AE 1292 G0

Type: TC, Shaft diameter: 25, Outside diameter: 35, Width: 6

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
25	35	6	AE 1292 G0	—	—	—
25	38	7	AE 1306 K0 ※	—	—	—
25	38	8	AE 1307 E1	—	—	—
25	40	7	AE 1313 E2	—	—	—
25	40	8	AE 1314 A0 ※	AE 1314 A1	AE 1314 A8	AE 1314 J1 ※
25	40	10	AE 1315 F0	—	—	—
25	42	8	AE 1322 F2	—	—	—
25	42	11	AE 1325 E0	—	—	—
25	45	7	AE 1334 E0	—	—	—
25	45	8	AE 1335 E0 ※	—	—	—
25	45	10	AE 1337 F0	—	—	—
25	45	11	AE 1338 A0	—	AE 1338 A2	AE 1338 G2
25	45	12	AE 1339 E0	—	—	—
25	46	7	AE 1344 E0	—	—	—
25	47	7	AE 1350 E1	—	—	—
25	47	8	AE 1351 E2	—	—	—
25	48	7	AE 1356 E0	—	—	—
25	49	12	AE 1358 E0	—	—	—
25	50	12	AE 1363 E0	—	—	—
25	52	10	AE 1377 F0	—	—	—
26	38	7	AE 1463 E0	—	—	—
26	40	7	AE 1467 E0	—	—	—
26	42	8	AE 1474 A0 ※	AE 1474 A1	—	—
26	48	11	AE 1481 E0	—	—	—
26	52	8	AE 1484 E1	—	—	—
27	42	7	AE 1510 E0	—	—	—
27	47	11	AE 1518 A0	—	—	—
28	40	8	AE 1538 E5	—	—	—
28	42	7	AE 1543 E1	—	—	—
28	42	8	AE 1544 F0	—	—	—
28	44	8	AE 1545 F0	—	—	—
28	44	11	AE 1546 E0	—	—	—
28	45	8	AE 1550 F4	AE 1550 E0	—	—
28	45	11	AE 1553 F0	—	—	—
28	47	7	AE 1557 E1	—	—	—
28	47	8	AE 1558 F0	—	—	—
28	48	8	AE 1562 F1	—	—	—
28	48	11	AE 1563 A0	—	AE 1563 A2	—
29	45	9	AE 1630 E0	—	—	—
30	42	8	AE 1666 F0	—	—	—
30	45	8	AE 1679 A0 ※	AE 1679 A1	AE 1679 A4	—
30	45	11	AE 1681 E1	—	—	—
30	46	7	AE 1688 E0	—	—	—
30	46	9	AE 1689 E1	—	—	—
30	46	10	AE 1690 E0	—	—	—

TC Type



TC type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 149.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AE 1692 E1

Type: TC, Shaft diameter: 30, Outside diameter: 47, Width: 8

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
30	47	8	AE 1692 E1	—	—	—
30	47	10	AE 1693 E1	—	—	—
30	48	7	AE 1699 E1	—	—	—
30	48	8	AE 1700 E0	—	—	—
30	48	11	AE 1702 E0	—	—	—
30	50	7	AE 1704 E0 ※	—	—	—
30	50	8	AE 1705 G0	AE 1705 F0	—	—
30	50	11	AE 1709 A0 ※	—	AE 1709 A2	AE 1709 J2
30	50	13	AE 1712 E0	—	—	—
30	52	8	AE 1720 E0	—	—	—
30	52	11	AE 1723 F0	—	—	—
30	52	12	AE 1724 E0	—	—	—
30	55	12	AE 1736 E1	—	—	—
30	55	14	AE 1738 E0	—	—	—
31	45	9	AE 1794 E0	—	—	—
32	48	8	AE 1894 G0 ※	—	—	—
32	50	10	—	AE 1896 E0	—	—
32	52	8	AE 1902 E0	AE 1902 G0	—	—
32	52	11	AE 1904 A0	AE 1904 A1	AE 1904 A7	—
32	54	10	AE 1910 E0	—	—	—
33	50	11	AE 1935 E1	—	—	—
34	52	11	AE 1975 E0	—	—	—
34	54	11	AE 1978 A0	—	—	—
35	48	8	AE 2048 K0	—	—	—
35	50	7	AE 2056 E0 ※	—	—	—
35	50	8	AE 2057 A0 ※	AE 2057 H0	AE 2057 F1	—
35	50	12	AE 2061 E0	—	—	—
35	52	7	AE 2066 E0	—	—	—
35	52	8	AE 2067 E1 ※	—	—	—
35	52	9	AE 2068 E0	—	—	—
35	52	11	AE 2071 F0	—	—	—
35	52	12	AE 2072 E0	—	—	—
35	55	8	AE 2081 E0	—	—	—
35	55	9	AE 2083 E1	—	—	—
35	55	10	AE 2084 E0	—	—	—
35	55	11	AE 2085 A0	AE 2085 A1	AE 2085 Q2	AE 2085 K4
35	55	12	AE 2086 E1	—	—	—
35	60	12	AE 2107 E1	—	—	—
35	60	14	AE 2108 E0	—	—	—
35	62	12	AE 2121 F1	—	—	—
36	58	12	AE 2170 E0	—	—	—
37	53	7	AE 2196 E0	—	—	—
38	50	8	AE 2218 E0	—	—	—
38	55	8	AE 2230 E0	AE 2230 H0	—	—
38	55	9	AE 2231 F0	—	—	—

TC Type



TC type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AE 2238 E0

Type: TC, Shaft diameter: 38, Outside diameter: 58, Width: 7

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
38	58	7	AE 2238 E0	—	—	—
38	58	8	AE 2239 E0	—	—	—
38	58	11	AE 2240 A0	AE 2240 A1	AE 2240 A7	—
38	58	13	AE 2242 E0	—	—	—
38	60	11	AE 2245 E0	—	—	—
38	62	9	AE 2249 E0	—	—	—
38	62	11	AE 2250 E0	—	—	—
40	52	8	AE 2343 E0	—	—	—
40	55	8	AE 2359 H0 ※	—	—	—
40	55	9	AE 2361 E0	—	—	—
40	56	10	AE 2366 E0	—	—	—
40	58	8	AE 2369 A0 ※	AE 2369 A1	AE 2369 A9	—
40	58	12	AE 2372 E0	—	—	—
40	60	12	AE 2379 E0	—	—	—
40	62	8	AE 2386 H1	—	—	—
40	62	11	AE 2388 A0	AE 2388 A1	AE 2388 A6	—
40	62	12	AE 2390 K0 ※	—	—	—
40	63	7	AE 2396 F0 ※	—	—	—
40	64	12	—	AE 2398 E0	—	—
40	65	10	AE 2402 E0	—	—	—
40	65	12	AE 2403 F0	—	—	—
40	65	14	AE 2405 E1	—	—	—
42	55	9	AE 2483 E0	—	—	—
42	60	9	AE 2493 E0	AE 2493 F0	—	—
42	65	9	AE 2504 F0	—	—	—
42	65	12	AE 2507 A0	AE 2507 A1	AE 2507 A2	—
44	60	9	AE 2557 E2	—	—	—
44	62	10	AE 2560 E0	—	—	—
45	60	9	AE 2643 E1 ※	—	—	—
45	62	9	AE 2651 A0 ※	AE 2651 A1	AE 2651 A8	AE 2651 F4
45	68	9	AE 2666 E0	—	—	—
45	68	12	AE 2668 A0	AE 2668 A1	AE 2668 H0	—
45	68	14	AE 2670 E0	—	—	—
45	70	12	AE 2676 E0	—	—	—
45	70	14	AE 2677 E0	—	—	—
45	72	12	AE 2685 H0	—	—	—
46	64	11	AE 2716 E0	—	—	—
48	62	9	AE 2775 E0	—	—	—
48	65	9	AE 2780 F0	—	—	—
48	70	9	AE 2788 H1	—	—	—
48	70	12	AE 2791 A0	AE 2791 A1	AE 2791 A2	—
48	70	14	AE 2793 E0	—	—	—
49	70	11	AE 2808 E0	—	—	—
50	68	9	AE 2847 A0 ※	AE 2847 A7	—	—
50	68	10	AE 2848 G0	—	—	—

TC Type



TC type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.


■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AE 2854 E0

Type: TC, Shaft diameter: 50, Outside diameter: 70, Width: 10

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
50	70	10	AE 2854 E0	—	—	—
50	70	11	AE 2856 E0	—	—	—
50	70	12	AE 2857 E0	—	—	—
50	72	9	AE 2861 E1 ※	—	—	—
50	72	10	AE 2862 E1 ※	—	—	—
50	72	12	AE 2864 A0 ※	AE 2864 A1	AE 2864 A9	AE 2864 J1
50	80	12	AE 2887 E0	—	—	—
50	80	14	AE 2888 E0	—	—	—
52	70	9	AE 2959 H1	—	AE 2959 E0	—
52	75	9	AE 2965 F1	—	—	—
52	75	12	AE 2967 A0	AE 2967 A1	AE 2967 A2	—
52	75	14	AE 2969 E0	—	—	—
52	78	12	AE 2972 E0	—	—	—
54	70	9	AE 3010 E0	—	—	—
55	72	9	AE 3040 A0 ※	AE 3040 A1	AE 3040 A7	—
55	72	12	AE 3042 E2	—	—	—
55	75	9	AE 3045 E0	—	—	—
55	78	12	AE 3055 A0	AE 3055 A1	AE 3055 A9	AE 3055 E2
55	78	14	AE 3056 E0	—	—	—
55	79	13	AE 3059 E0	—	—	—
55	80	10	AE 3061 E0	—	—	—
55	80	12	AE 3062 E1	—	—	—
55	85	14	AE 3072 F0	—	—	—
56	72	9	AE 3092 E2	—	—	—
56	78	9	AE 3093 E0	—	—	—
56	78	12	AE 3094 E0	—	—	—
57	77	12	—	—	AE 3106 E2	—
58	75	9	AE 3148 F1	—	—	—
58	80	9	AE 3152 E0	—	—	—
58	80	12	AE 3154 A6	AE 3154 A7	—	—
58	90	11	AE 3159 E0	—	—	—
60	75	9	AE 3193 F0	—	—	—
60	78	9	AE 3204 E0	—	—	AE 3204 G2
60	80	12	AE 3213 E5	—	—	—
60	80	13	AE 3215 E0	—	—	—
60	82	9	AE 3220 E0	—	—	—
60	82	12	AE 3222 A0	AE 3222 A1	AE 3222 A2	AE 3222 G0 ※
60	82	14	AE 3224 E0	—	—	—
60	85	12	AE 3234 F2	AE 3234 E0	—	—
60	90	11	AE 3241 E1	—	—	—
60	90	13	AE 3243 E0	—	—	—
60	90	14	AE 3244 E0	—	—	—
62	80	9	AE 3290 E3	—	—	—
62	85	9	AE 3295 E0	—	—	—
62	85	12	AE 3297 A0	AE 3297 A1	—	—

TC Type



TC type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.

■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AE 3316 F0


Type: TC, Shaft diameter: 63, Outside diameter: 80, Width: 9

14

TC type

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
63	80	9	AE 3316 F0	—	—	—
63	85	12	AE 3321 E0	—	—	—
65	88	12	AE 3400 A0	AE 3400 A1	AE 3400 A7	AE 3400 F1
65	88	14	AE 3402 E0	—	—	—
65	90	13	AE 3409 A0	AE 3409 A1	AE 3409 A6	AE 3409 F4 ※
65	95	14	AE 3414 F1	—	—	—
68	90	12	AE 3459 A5	AE 3459 A1	—	—
68	95	13	AE 3463 F0	—	—	AE 3463 E0
70	88	12	AE 3505 F3	—	—	AE 3505 G3
70	90	12	AE 3513 E0	—	—	—
70	92	12	AE 3519 A0	AE 3519 A1	AE 3519 A7	AE 3519 M3
70	92	14	AE 3521 E0	—	—	—
70	95	13	AE 3527 E0	AE 3527 A1	AE 3527 A9	—
70	100	13	AE 8520 E2	—	—	—
71	95	13	AE 3549 E0	—	—	—
75	95	13	AE 3611 E0	—	—	—
75	100	13	AE 3618 A0	AE 3618 A1	AE 3618 A2	AE 3618 F3
80	100	12	AE 3733 E0	—	AE 3733 G1	—
80	100	13	AE 3734 E0	AE 3734 F0	—	—
80	105	13	AE 3744 A0 ※	AE 3744 A1	AE 3744 A7	—
80	105	15	AE 3746 F0	—	—	—
80	115	15	AE 3761 E0	—	—	—
85	110	13	AE 3842 A0	AE 3842 A1	AE 3842 F0	—
85	110	15	AE 3844 E0	—	—	—
85	115	15	AE 3852 E0	—	—	—
85	120	15	AE 3855 E0	—	—	—
90	115	13	AE 3932 A9	AE 3932 A1	AE 3932 S1	AE 3932 A6
90	115	15	AE 3934 E0	—	—	—
90	120	13	AE 3938 E0	—	—	—
90	120	15	AE 3939 E0	—	—	—
90	125	15	AE 3944 F0	—	—	—
90	125	17	AE 3945 E0	—	—	—
90	135	15	AE 3951 E0	—	—	—
95	115	13	AE 3984 E0	—	—	—
95	120	13	AE 3994 A0	AE 3994 A1	AE 3994 F1	—
95	120	15	AE 3995 E0	—	—	—
95	130	15	AE 4007 E0	—	—	—
100	125	13	AE 4063 F0 ※	AE 4063 G0	AE 4063 J0	AE 4063 I0
100	125	15	AE 4065 E0	—	—	—
100	135	15	AE 4079 E0	—	—	AE 4079 F1
105	135	14	AE 4153 E0 ※	—	AE 4153 H2	—
105	140	15	AE 4161 E0	—	—	—
110	140	14	AE 4212 H7	AE 4212 F1	—	—
110	145	15	AE 4221 E0	—	—	—
112	145	14	AE 4237 E0	—	—	—

TC Type



TC type

- The sectional view on the right shows the typical profile of the seal type.
- Please refer to page 25 for the respective advantages and disadvantages of Types B and C.
- Check the guide to allowable operating conditions on pages 10 and 11 for relevant information on the seal selected before use.
- If there is an "※" at the end of the part number, as this indicates that an SUS spring specification is available, we ask that you refer to the introduction on SUS spring specifications on page 150.

■ When ordering, please indicate the NOK part number and the relevant dimensions.

Order Example NOK Part Number: AE 4279 E0

Type: TC, Shaft diameter: 115, Outside diameter: 140, Width: 15

Dimensions			Part Number			
Shaft diameter d	Outside diameter D	Width b	Nitrile (NBR) shaft diameter of 150 mm or less: A727 shaft diameter over 150 mm: A941	Acrylic (ACM) T303	Silicon (VMQ) S728	Fluorocarbon (FKM) F585
115	140	15	AE 4279 E0	—	—	—
115	145	14	AE 4282 E0	—	—	—
120	150	14	AE 4346 H0	—	—	—
120	155	16	AE 4355 E0	—	—	—
125	155	14	AE 4399 F0	—	AE 4399 I0	—
125	155	16	AE 4400 F0	—	—	—
130	160	14	AE 4451 F0 ※	—	AE 4451 H1	—
135	165	14	AE 4498 E2	—	—	—
140	160	14	AE 4535 G0	—	—	—
140	170	14	AE 4542 E0 ※	—	—	—
140	185	16	AE 4558 E0	—	—	—
145	175	14	AE 4581 E0	—	AE 4581 G0	—
145	190	16	AE 4588 E0	—	—	—
150	180	14	AE 4624 F6	—	—	—
150	180	16	AE 4626 F0	—	—	—
155	180	15	AE 4666 E0	—	—	—
155	200	20	AE 4678 E0	—	—	—
160	190	15	AE 4712 E1	—	—	—
170	200	16	AE 4795 E0 ※	—	—	—
170	205	16	AE 4800 E0	—	—	—
180	210	16	AE 4898 E5	—	—	—
185	210	15	AE 4943 E1	—	—	—
190	225	16	AE 4983 P2	—	—	—
200	230	15	AE 5053 E2 ※	—	—	—
200	240	20	AE 5068 E2	—	—	—
220	250	16	AE 5205 E1	—	—	—
220	255	18	AE 5208 G3	—	—	—
220	275	23	AE 5224 E0	—	—	—
230	270	16	AE 5289 E0	—	—	—
230	270	20	AE 5290 E0	—	—	—
240	270	20	AE 5341 E0	—	—	—
240	275	16	AE 5346 E0	—	—	—